



NOTE:
TYPICAL INSTALLATION PLACES FERTILIZER ON CENTERLINE WITH CENTERLINE OF MOUNTING BOLTS OFF CENTER

**RH UNIT SHOWN
LH IS MIRROR OPPOSITE**

**OPTIONAL TRASHWHEEL
SHOWN**

WEIGHT= 475LBS (NO ROW CLEANER)

MAX UPWARD LIFT ON FRAME= 500LBS

TOLERANCES - ALL DIMENSIONS ARE IN INCH SYSTEM - UNLESS OTHERWISE NOTED:
1-PLACE DECIMALS = ± .06 2-PLACE DECIMALS = ± .03 3-PLACE DECIMALS ± = .015

REV	DATE	DESCRIPTION	BY

DAWN EQUIPMENT COMPANY	
BOX 497 SYCAMORE, ILLINOIS 60178 USA	
DRWN: JDB	SCALE: 1/12
DATE: 8/4/11	APPROVED: JDB
MATL: BOM	FINISH: PWDR COAT BLCK
NAME: 6000 MOUNTING SPECS	DRAWING NUMBER: 6000R (2011)
	REV: 3

PLEASE NOTE:
THIS DRAWING IS THE PROPERTY OF THE DAWN EQUIPMENT COMPANY AND IS NOT TO BE USED FOR ANY PURPOSE DETRIMENTAL TO ITS INTEREST. ALL DESIGN RIGHTS ARE RESERVED.